

LA-UR-22-21473

Approved for public release; distribution is unlimited.

Title: K-Modules: Capacitive Energy Modules for Pulsed Power Applications

Author(s): Dighe, Kalpak Arvind

Intended for: F0r discussion at DisrupTech program

Issued: 2022-02-22



Los Alamos National Laboratory, an affirmative action/equal opportunity employer, is operated by Triad National Security, LLC for the National Nuclear Security Administration of U.S. Department of Energy under contract 89233218CNA000001. By approving this article, the publisher recognizes that the U.S. Government retains nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes. Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy. Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.

K-Modules: Capacitive Energy Modules for Pulsed Power Applications

Kalpak A. Dighe; J-Division; kdighe@lanl.gov; (505) 665 1701





PROBLEM

- Current design of pulsed power system in Febetrans (X-ray generating machines) has **not changed in 40 yrs.**
- Only **one supplier since 1970's** for replacement parts.

APPLICATION

- Users who have already expressed interest in the developed technology are DOE labs, DoD (US Air Force, US Army) as well as private sector companies, e.g., Northrup Grumman and Boeing.
- Developed technology retains same form factor of current modules, thus simple drop-in process 'OUT with the old, IN with the new' for the Febetrans. Customized modules with varied outputs can easily be fabricated for other applications.
- Entities using Febetrans for X-ray or electron beam applications will benefit from this technology. Alternate pulsed power applications are being investigated (e.g. accelerators).




SOLUTION

- The technology is a module containing an assembly of capacitors. The modules are meant to be daisy-chained to form a Marx bank (bank of capacitors). Discharging the bank produces a high voltage, high current pulse, that when coupled to an X-ray or electron beam tube, generates X-rays or an intense electron beam.
- **Number of modules in the stack can be varied** to meet different pulsed power applications.
- The technology **addresses the need for an alternate provider** with a new, robust design. The technology has the potential to **extend the life** of the X-ray radiography program in the country.
- **K-Module has been pulsed over 400 times in the past two years in an operational unit at LANL's firing point, thereby proving its robustness and performance.**

K-Modules: Capacitive Energy Modules for Pulsed Power Applications

Kalpak A. Dighe; J-Division; kdighe@lanl.gov; (505) 665 1701

BENEFITS



Higher output



Modular, thus scalable output



Serviceable




Reusable components

COMPETITIVE ADVANTAGE

- Provides much needed **design upgrade** - present design is **40+ years old**.
- Stores **twice the energy** and provides higher voltage, higher current and **~30 % higher X-ray dose** than the present design.
- Provides end-users with an **alternate procurement source** - there has been **only one supplier for 40+ years**.
- New modules are assembled with COTS components and **does not involve chemical processes** that are needed currently.
- Reduced manufacturing time (e.g. **5 months** to manufacture 100 K-modules **vs 14 months** to manufacture 100 of the current modules)



Stack of 15 modules undergoing testing



TECHNOLOGY STATUS AND NEXT STEP

Feb-Jun 2022

- Continue lab experiments
- Refine and finalize designs
- Investigate 'other than X-ray' applications
- Customer discovery

Jul-Nov 2022

- File non-provisional patent
- File for small business start-up
- Commercialize products

TECHNOLOGY READINESS LEVEL AND IP

- Between **TRL5** and **TRL6**. Operation of multiple modules have been demonstrated in the laboratory; performance and quantitative data have been logged.
- **LANL/TRIAD has already filed an application for a provisional patent (S167562).**